

HANCO Quiet Power Rental Series Generators

QP25

Standby Rating: 25kVA / 20kw

Prime Rating: 23kVA / 19kw

QP35

Standby Rating: 35kVA / 28kw

Prime Rating: 32kVA / 26kw



GENERATOR FEATURES

- Perkins Tier 4i/Flex engine
- Brushless Alternator with PMG motor starting performance
- Digital engine generator controller with 1 button Start/Stop and 2 wire Autostart for ease of use
- Multi-voltage switch with utility power in both 120/240 and 120/208 modes
- Full capacity power outlet lugs, and utility outlets for customer connections
- 12 gauge, powder coated, lockable, sound attenuated enclosure
- Large capacity dual containment fuel cell with environmental containment basin
- Single point lift
- Available with or without trailer
- Custom branding options available

Perkins Diesel Engines

- Heavy Duty, 4-cycle, indirect Injection, diesel engine for maximum reliability
- EPA tier 4i FLEX certified
- Fuel efficient
- Robust construction
- Mechanical fuel system and governor control maintains frequency from no load to full load
- Up to 500 hour service Intervals

Alternators

- Oversized PMG alternators for better motor starting

Engine/Generator Controls

- Hanco Tough Series TGS410 Digital Genset controller for precise engine and generator management and alternator protection

Model	Voltages	Standby kVA/KW	Prime kVA/KW	Engine Model	Alternator
QP25	120/208 240//480	25kVA / 20KW	23 kVA / 18 KW	404D-22G	Hanco Meccalte
QP35	120/208 240/480	35 kVA / 28 KW	33 kVA / 26 KW	404D-22TG	Hanco Meccalte

HANCO Quiet Power Rental Series QP25 and QP35

Engine Data	25 kVA	35 kVA
Engine Mfg	PERKINS	PERKINS
Model Number	404D-22G	404D-22TG
Spec #	GN71022N	GP71009N
Prime output HP	29.5	40.5
Standby Output HP	32.6	44.7
Emissions certification	Tier 4i / Flex	Tier 4i / Flex
Fuel tank capacity - Gallons	65	65
Fuel consumption at prime rating	1.6 gal	2.19 gal
25% load		
50% load	.93	1.34
75% load	1.27	1.64
100% load	1.82	2.46

Alternator data	120/208	240/480	120/208	240/480
Available voltages				
277/480 volt prime amps		30.1		39
277/480 volt standby amps		27.7		42
120/208 v prime amps		63.9		92
120/208 volt standby amps		69.5		97
120/240 volt prime amps		55.4		79
120/240 volts standby amps		60.2		84

Enclosure data		
Length - Enclosure only	80"	80"
Width	38"	38"
Height	59.625"	59.625"
Weight-dry	2400 lbs	2450 lbs
Length with trailer	119.625"	192.625"
Width with trailer	60"	60"
Height with trailer	75.875"	75.875"
Weight with trailer	2700 lbs	2750 lbs
Weight with trailer ready to run	3170 lbs	3230 lbs

Sound dBA level @ 23 ft.	59 dBA	59 dBA
---------------------------------	--------	--------

Distributed By:

HANCO Generating Systems
 11690 N. 132nd Ave. Surprise, AZ 85379
 877-779-3581 - www.southwestProducts.com

* Specifications and descriptions are accurate as known at the time of publication but are subject to change without notice. Illustrations may include optional equipment and accessories.