

# ISUZU 3CD1

32 Horsepower  
Industrial Diesel



Performance Curve Not Yet  
Available at Time of Publish

## MAIN SPECIFICATIONS

Type	3 Cylinder, 4 Cycle, Water Cooled, OHV, In- Line, Direct Injection,
Bore & Stroke	3.30 x 3.54 in. (84mm x 90mm)
Engine Displacement	1.5 L
Compression Ratio	19.0:1
Dry Weight	341 lb. (155 kg)
Dimensions (L x W x H)	23.89 x 20.39 x 26.85 in. (607 x 518 x 682mm)
Coolant Capacity	2.13 qt. (2 L)
Lube Oil Capacity	7.14 qt. (6.7 L) (less filter)

## MAIN FEATURES

Alternator	12V – 40A
Voltage Regulator	Internal
Starter	12V – 1.7kW
Exhaust Outlet	Rear Upward
Air Inlet	Center Upward
Flywheel Housing	SAE #5 Type
Flywheel	SAE Type for 7.5"
Oil Pan	30° Inclination All Directions
Fan	14.17 in. (360mm) Suction

## INDUSTRIAL RATING\*

Rated Output	32 BHP @ 3000 RPM
Max Torque	72.2 lb. ft. @ 1200 RPM

\*SAE J1995 Gross BHP

Specifications subject to change without notice.