

# 400 Series

## 404D-22TG

### Diesel Engine - Electropak

27.0 kWm @ 1500 rev/min

32.6 kWm @ 1800 rev/min

#### Powered by your needs

- The 404D-22TG is a new addition to the 400D range of Electropaks and is a powerful but quiet 2.2 litre turbocharged 4-cylinder compact package
- Electronically governed and switchable 1500/1800 rpm

#### Compact, Clean, Efficient Power

- Design features on the 404D-22TG Electropak ensures clean rapid starting in all condition whilst delivering impressive performance with low operating costs in a small, efficient package size

#### Lower Operating Costs

- The compact package Size makes Installation and transportation easier and more cost effective
- Operating and maintenance costs are reduced through excellent fuel and oil economy
- Service intervals are set at 500 hours as standard and Perkins provides comprehensive warranty cover for two years, with three years on major engine components. A low usage warranty package is also available

#### Long-term Power Solution

- The 400D range of Electropaks has been designed to fully comply with stringent EU and EPA emissions regulations, providing an emissions compliant power solution for the future

#### World-class Product Support

- At Perkins we are constantly researching, developing and investing in our products and services. Total worldwide support is provided through a network of distributors and service outlets, providing access to over 50,000 parts and exchange units 24 hours a day, 365 days a year. This support is enhanced by TIPSS (The Integrated Parts and Service System). TIPSS enables customers to electronically specify and order parts as well as service 400 Series engines with online guides and service tools

#### Emissions statement

- Certified against the requirements of EU2007 (EU 97/68/EC Stage II) and EPA Interim Tier 4 (EPA 40 CFR Part 1039 Interim Tier 4) legislation for non-road mobile machinery, powered by constant speed engines

The 400 Series engine family continues to set new standards in the compact engine market. Developed alongside customers to fulfill their needs in the Genset, Compressor, Agricultural and general Industrial markets.

These new Electropaks provide compact power, from a robust family of 3 and 4 cylinder diesel engines designed to provide economic and durable operation at Prime and Standby duties, hitting the key power nodes required by the power generation industry.

Engine Speed	Type of Operation	Typical Generator Output (Net)		Engine Power			
				Gross		Net	
		kVA	kWe	kWm	bhp	kWm	bhp
1500	Prime Power	27.4	21.9	25.2	33.7	24.9	33.4
	Standby Power	30.1	24.1	27.7	37.1	27.4	36.7
1800	Prime Power	32.9	26.3	30.3	40.5	29.6	38.5
	Standby Power	36.3	29.0	33.3	44.7	32.6	42.8

The above ratings represent the engine performance capabilities to conditions specified in ISO 8528/1, ISO 3046/1:1986, BS 5514/1.

Derating may be required for conditions outside these; consult Perkins Engines Company Limited.

Generator powers are typical and are based on typical alternator efficiencies and a power factor (cos  $\theta$ ) of 0.8.

Fuel specification: BS 2869: Part 2 1998 Class A2 or ASTM D975 D2.

Rating Definitions

**Prime Power:** Power available at variable load in lieu of a main power network. Overload of 10% is permitted for 1 hour in every 12 hours operation.

**Standby (maximum):** Power available at variable load in the event of a main power network failure. No overload is permitted.

Photographs are for illustrative purposes only and may not reflect final specification.

All information in this document is substantially correct at time of printing and may be altered subsequently

Publication No. 1913/02/09 Produced in England ©2009 Perkins Engines Company Limited

# 400 Series

## 404D-22TG

### Standard ElectropaK Specification

#### Air Inlet

- Mounted air filter

#### Fuel System

- Electronically governed cassette type fuel injection pump
- Split element fuel filter

#### Lubrication System

- Wet steel Sump with filler and dipstick
- Spin-on full-flow lub oil filter

#### Cooling System

- Thermostatically-controlled system with belt driven coolant pump and pusher fan
- Mounted radiator, piping and guards

#### Electrical Equipment

- 12 volt starter motor and 12 volt 65 amp alternator with DC output
- Oil pressure and coolant temperature switches
- 12 volt shut-off solenoid energised to run
- Glow plug cold start aid and heater/starter switch

#### Flywheel and Housing

- 1500/1800 rev/min
- High inertia flywheel to SAE J620 Size 7½ Heavy
- Flywheel housing SAE 4 Long

#### Mountings

- Front and rear engine mounting bracket

#### Optional Equipment

- Workshop manual
- Parts book

988 mm	588 mm	969 mm

Engine Speed	Fuel Consumption			
	1500 rev/min		1800 rev/min	
	g/kWh	l/hr	g/kWh	l/hr
Standby	287	9.5	247	9.9
Prime power	271	8.2	241	8.8
75% of prime power	255	5.8	237	6.4
50% of prime power	262	3.9	249	4.5

### General Data

Number of cylinders	4
Cylinder arrangement	Vertical in-line
Cycle	4 stroke
Aspiration	Turbocharged
Combustion system	Indirect injection
Compression ratio	23.3:1
Bore and Stroke	84 x 100 mm
Displacement	2.216 litres
Direction of rotation	Anti-clockwise viewed on flywheel
Cooling system	Water cooled
Total coolant capacity	9.4 litres
Total Lubrication system capacity	10.6 litres
Length	988 mm
Width	588 mm
Height	969 mm
Total weight (dry)	260 kg

Final weight and dimensions will depend on completed specification.



### Perkins Engines Company Limited

Peterborough PE1 5NA  
 United Kingdom  
 Telephone +44 (0)1733 583000  
 Fax +44 (0)1733 582240  
[www.perkins.com](http://www.perkins.com)

Distributed by